

Material Safety Data Sheet

SECTION I CHEMICAL and COMPANY IDENTIFICATION

PRODUCT: *Alphatac 100 WW*
CHEMICAL NAME: Hydrocarbon Resin
COMMON/GENERIC NAME: C-5 Resin
CHEMICAL FAMILY: *Petroleum Hydrocarbon*
MANUFACTURER: Rezkem, LLC. Customer Service (330) 653 - 9104
EMERGENCY NUMBERS: CHEMTREC 800-424-9300
CANUTEC(Canada) 613-996-6666

SECTION II Hazardous / INGREDIENT INFORMATION

<u>COMPOSITION:</u>		<u>OSHA PEL</u>	<u>Cercla RQ</u>
Naphthalene	<0.05 wt %	10 ppm	100 lbs
C.A.S.#	91 - 20 - 3		
C5 Petroleum Hydrocarbon	>99%	ND	ND
CAS #	Proprietary		

SECTION III/IV HAZARDS / FIRST AID PROCEDURES

EMERGENCY OVERVIEW: A light colored, Amber flake/prill, which may cause mild irritation to eyes, skin, and nasal passages. Ingestion and prolonged contact should be avoided.

EYE: Flush eyes with water for 15 min. Call a physician if irritation develops.

SKIN: Wash skin with soap and water. If in contact with hot product, treat as a burn.

INGESTION: Do not induce vomiting. Never give anything by mouth to unconscious person. Seek medical attention.

INHALATION: Remove to fresh air; give artificial respiration or oxygen if necessary.

TOXICITY: No significant adverse effects expected. Not considered toxic/hazardous.

CARCINOGENICITY: May contain a small amount of naphthalene which is listed in group 2B by IARC. Not listed by NTP or OSHA

IN ALL CASES OF EMERGENCY, CONTACT A PHYSICIAN

SECTION V FIRE AND EXPLOSION INFORMATION

FLASH POINT 450°F COC

FIRE-FIGHTING PROCEDURES: Use Chemical foam, CO₂, Dry Chemical, water fog. Treat as burning oil. Keep drums as cool as possible to avoid expansion, explosions, and splattering.

HAZARDOUS COMBUSTION PRODUCTS: This product will decompose under extreme temperatures forming oxides of carbon.

PROTECTIVE EQUIPMENT: Full eye protection and protective clothing are required for all indoor/outdoor fires and spills.

AVOID CREATING AN AIRBORNE DUST OF ALPHATAC AS IT COULD BE AN EXPLOSION HAZARD!

SECTION VI SPILLS AND ENVIRONMENTAL INFORMATION

SPILL OR LEAK PRECAUTIONS: Wear appropriate protective clothing, gloves and equipment. Contain spill with inert absorbent or earth. Transfer to secure containers and dispose of according to local and state regulations. Thought should always be given to collecting the material in such a manner that it could be recycled. Clean/scrub affected area with detergent. Prevent run-off into sewers or natural waterways. Spills in excess of the RQ must be reported to the local emergency response organizations. Major spills should also be reported to the National Response Center. Spills with potential to contaminate coastal waterways must be reported to the U.S. Coast Guard (800-424-8802)

WASTE DISPOSAL: All containers should be effectively labeled to facilitate the appropriate disposal or reclaim.

SECTION VII HANDLING AND STORAGE

Store in sealed containers in dry, ambient temperature conditions. Avoid creation of dust as it can be an explosion hazard in the presence of an ignition source.

SECTION VIII EXPOSURE CONTROLS AND PERSONAL PROTECTION

VENTILATION: Use only where sufficient ventilation exists to keep exposure levels of fumes and dust below recommended levels.

RESPIRATORY AND PERSONAL PROTECTION: Respirators should be selected when TWA exceeded. Avoid hot vapors when mixing or packaging. Safety glasses with side shields; gloves, boots and apron as appropriate.

FACILITIES: There should be a shower facility and eyewash in the building where this product is being stored and handled. Exercise good chemical handling practice.

SECTION IX PHYSICAL AND CHEMICAL INFORMATION

Appearance: Light colored, amber prill/flake	Evaporation Rate: < 1 (butyl acetate=1)
Specific Gravity @25°C = 0.97	Boiling Point: NA
Vapor Pressure: ND	Refractive Index 25°C: NA
Viscosity cPs (25°C) = NA	Solubility in Water: <<0.1%

SECTION X STABILITY AND REACTIVITY

Under normal storage conditions, this product a) is stable; b) will not polymerize or exotherm; c) should be kept away from extreme heat, strong oxidizers and bases; d) this product decomposes under high temperature and hydrolyses in humid conditions.

SECTION XI TOXICOLOGICAL INFORMATION

Low hazard for inhalation, eyes, skin, ingestion when handled by trained personnel.

SECTION XII ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: NA

Rezkem Chemicals
77 Milford Drive, Suite 258
Hudson Ohio 44236
330-653-9104

SECTION XIII

DISPOSAL CONSIDERATIONS

Incineration by a permitted hazardous waste facility in accordance with all regulatory requirements is the preferred method of disposal. Empty containers can be rinsed with a suitable solvent/surfactant and steamed to remove residual product and fumes before disposal or reuse in accordance with applicable regulations. For spill clean-up procedures see Sect.VI.

SECTION XIV

TRANSPORTATION INFORMATION

DOT: Not restricted. Label: Product trade name with chemical description.

CANADA TRANSPORT HAZ.GOODS: Not restricted.

AIR (IATA/ICAO): Not restricted. Label: Product trade name with chemical description.

EUROPEAN TRANSPORTATION: ADR/RID HAZ. CLASS: Not regulated.

US CUSTOMS: - HARMONIZED TARIFF CODE: 3911.10.00.00

EINECS:

SECTION XV

REGULATORY INFORMATION

OSHA: Not Determined

SARA TITLE III: - 311/312 CATEGORIES: Not listed.

“ “ - 313 Reportable ingredients: None

Not hazardous under the CFR 1910.1200

CERCLA RQ: Not applicable.

RCRA Status: Not Determined

TSCA REGULATORY: All intentional ingredients are listed in the TSCA Inventory.

CANADA WHMIS HAZARD SYMBOL AND CLASS: Not controlled

CANADA INGREDIENT DISCLOSURE LIST: Does not contain any ingredients on the IDL. All intentional ingredients are on the DSL.

** Naphthalene is known to the state of California to cause cancer. Naphthalene is on the following State Right to Know lists: Massachusetts, New Jersey and Pennsylvania

SECTION XVI OTHER INFORMATION

HMIS Label: Health: 0
Fire: 1
Reactivity: 0
Protection: B min.

Prepared: Feb. 1

The information presented herein, while not guaranteed, was prepared by technically knowledgeable personnel and to the best of our knowledge is true and accurate. It is not intended to be all inclusive and the manner and conditions of use and handling may involve other or additional considerations.

Rezkem Chemicals
77 Milford Drive, Suite 258
Hudson Ohio 44236
330-653-9104