



Milford Corporate Center
77 Milford Drive, Suite 258
Hudson Ohio 44236
330-653-9104

Current Issue Date:
May, 2015
Version Number 2

Product Data Sheet

Arotac™130 Hydrocarbon Resin

Arotac 130 is an aromatic C9 hydrocarbon resin. It is highly resistant to heat and UV. The product is soluble in most organic solvents, chemically neutral, water resistant and non-toxic. Arotac is recommended for use in: coatings, paints, contact adhesives, hot-melt adhesives, rubber and inks.

Physical Properties

Specifications

Softening Point, R&B°C (ASTM E-28 - 58)	130 ± 5
Color Gardner (50% in 100 Solvent) (ASTM D-1544)	6 - 18
Specific Gravity @ 25°C (ASTM D-71)	1.05 - 1.10
Acid Value (mg KOH/g) (ASTM D-974)	≤ 0.6
Ash Content % (ETM-E-99)	≤ 0.1

Form: Granular

Package: 25kg poly bags, super sacks, bulk

We believe the information contained in this document is reliable. However, this does not release our customers from the obligation to test the products supplied by us as to their suitability for intended process and end use. Since many of the applications, uses, and processing of the products are beyond our control, we cannot be held liable for any consequential service failures that occur.